

EN, This declaration of performance concerns to **GS insPIRe CH MAX** products - Self-supporting double skin metal faced insulating panels with PIR core (galvanized or stainless steel faces, yield strength ≥ 220 N/mm²), thickness (outer/inner) min. 0,5 / 0,4 mm and for all organic coatings. Modular width: 1000 or 1140 mm. Facing profile: L(linear), M(microprofiling), F(wavy), R(grooving), P(smooth). Certificate of constancy of performance no. 1487-CPR-174-02 issued by notified body ICiMB (no. 1487).



DECLARATION OF PERFORMANCE

no. CH/MAX/03/2022

Unique identification code of the product-type:

GS insPIRe CH [thickness d_N] **MAX** [modulus: 1000 or 1140] [outer/inner profil.: L,M,F,R,P / L,P]

Harmonised standard: EN 14509:2013

System/s of AVCP: System 1

Notified body/ies: ICiMB (No. 1487), FIRES (No. 1396)

Intended use/es: Internal and external walls, ceilings

Manufacturer:: GÓR-STAL Sp. z o.o., ul. Przemysłowa 11, 38-300 Gorlice, POLAND

Declared performance/s:

Unique identification code of the product-type		GS insPIRe CH100 MAX	GS insPIRe CH120 MAX	GS insPIRe CH160 MAX	GS insPIRe CH200 MAX	Classification
		modulus: 1000, 1140, profil.: L,M,F,R,P / L,P				
Thickness		100 mm	120 mm	160 mm	200 mm	EN 14509:2013
Essential characteristics / Parameters		Value of parameters				
Thermal properties						
Thermal conductivity, λ_D		W/m·K	0,019			
Thermal transmittance, $U_{d,s}$		W/m ² ·K	0,19	0,16	0,12	0,10
Mechanical properties						
Compressive strength (core)		MPa	0,10			
Tensile strength		MPa	0,060			
Shear strength		MPa	0,10	0,10	0,085	0,080
Shear modulus (core)		MPa	2,9	2,8	2,5	2,4
Bending resistance in the span	positiv.	kN·m	7,57	9,09	12,12	15,15
Bending resistance in the span	negativ.					
Bending resist. at an internal support	positiv.	kN·m	4,36	5,23	6,97	8,72
Bending resist. at an internal support	negativ.					
Bending resistance in the span	positiv.	kN·m	7,41	8,90	11,87	14,84
Bending resistance in the span	negativ.					
Bending resist. at an internal support	positiv.	kN·m	4,27	5,12	6,83	8,54
Bending resist. at an internal support	negativ.					
Creep coefficient			for t=2.000h: 0,84 (for 0,5/0,5); 1,22 (for 0,5/0,4)			
			for t=100.000h: 1,38 (for 0,5/0,5); 2,04 (for 0,5/0,4)			
Reduced long term shear strength (40%)		MPa	0,040	0,040	0,034	0,032
Reaction to fire (all applications)			B-s1,d0			
Fire resistance - horizontally			EI 30 / EW 30			
Fire resistance - vertically		NPD	EI 30 / EW 30			
Water permeability			NPD			
Water vapour permeability			„Impermeable”			
Air permeability			NPD			
Air permeability (with EPDM gasket)		(+)	C=0,0031 m ³ /(hPa ⁿ), n=0,8004			
		(-)	C=0,0528 m ³ /(hPa ⁿ), n=0,3110			
Luftschalldämmung			23(-2,-3) dB			
Schallabsorption			0,1 dB			
Masstoleranzen			„Pass” (Thickness: $\pm 2\%$)			
Duerhaftigkeit			„Pass”			
Gefährliche Substanzen			NPD			

Die Leistung des vorstehenden Produkts entspricht der erklärten Leistung/den erklärten Leistungen. Für die Erstellung der Leistungserklärung im Einklang mit der Verordnung (EU) Nr. 305/2011 ist allein der obengenannte Hersteller verantwortlich.

„GÓR-STAL” Sp. z o.o.
38-300 Gorlice, ul. Przemysłowa 11
tel. 018 353 98 00
REGON 852712117 NIP 738-19-45-154

DYREKTOR ZAKŁADU
Piotr Grzywa

Gorlice, 01.07.2025

signed for and behalf of the manufacturer by