

Maximum allowable loads for a given span length:

GS insPIRe® U60

module: 1000 mm

External cladding thickness [mm]:	0,5		
Internal cladding thickness [mm]:	0,5		
Outdoor temperature (summer/winter) [°C]:	55	65	80
Indoor temperature (summer/winter) [°C]:	25		
Minimum width of end support [mm]:	40		
Minimum width of the intermediate support [mm]:	60		

The minimum number of the screws on the end support :	2 + 1xPM-1
The minimum number of the screws on the intermediate support :	2 + 1xPM-1
Core material :	PIR
Cladding steel grade:	S220GD
Ultimate limit state (compare design loads)	ULS
Serviceability limit state (compare characteristic loads)	SLS

Static diagram	Colour group	Criterion	Maximum evenly distributed load [kN/m²]											
			Axial span of supports [m]											
			1,5	2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	6,5	
Single-span system	I	ULS	pressure	4,89	3,67	2,93	2,44	2,10	1,80	1,42	1,15	0,95	0,80	0,68
			suction	6,91	5,09	3,26	2,26	1,66	1,27	1,01	0,82	0,67	0,57	0,48
		SLS L/100	pressure	5,90	3,53	2,22	1,43	0,95	0,64	0,43	0,30	0,21	0,14	0,10
			suction	6,19	3,78	2,42	1,61	1,09	0,76	0,54	0,39	0,28	0,21	0,16
		SLS L/150	pressure	3,55	2,03	1,20	0,72	0,44	0,26	0,15	-	-	-	-
			suction	3,84	2,27	1,41	0,90	0,58	0,38	0,25	0,17	0,11	-	-
	SLS L/200	pressure	2,37	1,27	0,69	0,37	0,18	-	-	-	-	-	-	
		suction	2,66	1,52	0,90	0,54	0,33	0,19	0,11	-	-	-	-	
	II	ULS	pressure	4,89	3,67	2,93	2,44	2,10	1,80	1,42	1,15	0,95	0,80	0,68
			suction	6,91	5,09	3,26	2,26	1,66	1,27	1,01	0,82	0,67	0,57	0,48
		SLS L/100	pressure	5,90	3,53	2,22	1,43	0,95	0,64	0,43	0,30	0,21	0,14	0,10
			suction	5,90	3,53	2,22	1,43	0,95	0,64	0,43	0,30	0,21	0,14	0,10
		SLS L/150	pressure	3,55	2,03	1,20	0,72	0,44	0,26	0,15	-	-	-	-
			suction	3,55	2,03	1,20	0,72	0,44	0,26	0,15	-	-	-	-
	SLS L/200	pressure	2,37	1,27	0,69	0,37	0,18	-	-	-	-	-	-	
		suction	2,37	1,27	0,69	0,37	0,18	-	-	-	-	-	-	
	III	ULS	pressure	4,89	3,67	2,93	2,44	2,10	1,80	1,42	1,15	0,95	0,80	0,68
			suction	6,91	5,09	3,26	2,26	1,66	1,27	1,01	0,82	0,67	0,57	0,48
		SLS L/100	pressure	5,90	3,53	2,22	1,43	0,95	0,64	0,43	0,30	0,21	0,14	0,10
			suction	5,47	3,16	1,90	1,17	0,73	0,45	0,28	0,16	-	-	-
		SLS L/150	pressure	3,55	2,03	1,20	0,72	0,44	0,26	0,15	-	-	-	-
			suction	3,11	1,66	0,89	0,46	0,22	-	-	-	-	-	-
	SLS L/200	pressure	2,37	1,27	0,69	0,37	0,18	-	-	-	-	-	-	
		suction	1,94	0,90	0,38	0,11	-	-	-	-	-	-	-	

Multi-span system	I	ULS	pressure	3,25	2,37	1,85	1,45	1,01	0,75	0,57	0,45	0,37	0,31	0,26
			suction	2,76	2,07	1,66	1,20	0,84	0,62	0,48	0,38	0,31	0,26	0,22
		SLS L/100	pressure	6,74	4,54	3,20	2,32	1,71	1,28	0,98	0,75	0,59	0,46	0,37
			suction	6,94	4,70	3,33	2,42	1,80	1,36	1,05	0,82	0,65	0,52	0,42
		SLS L/150	pressure	4,22	2,82	1,96	1,40	1,02	0,75	0,56	0,43	0,33	0,25	0,19
			suction	4,42	2,97	2,09	1,51	1,11	0,83	0,63	0,48	0,37	0,30	0,24
	SLS L/200	pressure	2,96	1,95	1,35	0,94	0,67	0,48	0,35	0,25	0,19	0,14	0,10	
		suction	3,16	2,11	1,47	1,05	0,76	0,56	0,42	0,32	0,25	0,19	0,15	
	II	ULS	pressure	3,25	2,37	1,85	1,45	1,01	0,75	0,57	0,45	0,37	0,31	0,26
			suction	2,76	2,07	1,46	0,92	0,62	0,45	0,34	0,26	0,21	0,17	0,15
		SLS L/100	pressure	6,74	4,54	3,20	2,32	1,71	1,28	0,98	0,75	0,59	0,46	0,37
			suction	6,74	4,54	3,20	2,32	1,71	1,28	0,98	0,75	0,59	0,46	0,37
		SLS L/150	pressure	4,22	2,82	1,96	1,40	1,02	0,75	0,56	0,43	0,33	0,25	0,19
			suction	4,22	2,82	1,96	1,40	1,02	0,75	0,56	0,43	0,33	0,25	0,19
	SLS L/200	pressure	2,96	1,95	1,35	0,94	0,67	0,48	0,35	0,25	0,19	0,14	0,10	
		suction	2,96	1,95	1,35	0,94	0,67	0,48	0,35	0,25	0,19	0,14	0,10	
	III	ULS	pressure	3,25	2,37	1,85	1,45	1,01	0,75	0,57	0,45	0,37	0,31	0,26
			suction	2,76	1,86	0,90	0,49	0,29	0,18	0,12	-	-	-	-
		SLS L/100	pressure	6,74	4,54	3,20	2,32	1,71	1,28	0,98	0,75	0,59	0,46	0,37
			suction	6,43	4,31	3,01	2,15	1,57	1,16	0,87	0,66	0,51	0,40	0,31
		SLS L/150	pressure	4,22	2,82	1,96	1,40	1,02	0,75	0,56	0,43	0,33	0,25	0,19
			suction	3,92	2,58	1,77	1,24	0,87	0,63	0,45	0,34	0,25	0,18	0,13
	SLS L/200	pressure	4,22	2,82	1,96	1,40	1,02	0,75	0,56	0,43	0,33	0,25	0,19	
		suction	2,65	1,72	1,15	0,78	0,53	0,36	0,25	0,16	0,11	-	-	

I colour group:	very bright	RAL: 1015, 7035, 9002, 9010, 9016
II colour group:	bright	RAL: 5012, 9006, 6011
III colour group:	dark	RAL: 3000, 5010, 6029, 7016, 7024, 8017, 9007

In the case of dark colors, the total length of the board is limited. Details available from our sales representatives.

For other values of the internal temperature, thickness and material lining, etc., Please contact us to perform separate calculations.

Maximum allowable loads for a given span length:

GS insPIRe® U80

module: 1000 mm

External cladding thickness [mm]:	0,5		
Internal cladding thickness [mm]:	0,5		
Outdoor temperature (summer/winter) [°C]:	55	65	80
Indoor temperature (summer/winter) [°C]:	-20		
Minimum width of end support [mm]:	40		
Minimum width of the intermediate support [mm]:	60		

The minimum number of the screws on the end support :	2 + 1xPM-1
The minimum number of the screws on the intermediate support :	2 + 1xPM-1
Core material :	PIR
Cladding steel grade:	S220GD
Ultimate limit state (compare design loads)	ULS
Serviceability limit state (compare characteristic loads)	SLS

Static diagram	Colour group	Criterion	Maximum evenly distributed load [kN/m²]												
			Axial span of supports [m]												
			1,5	2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	6,5		
Single-span system	I	ULS	pressure	5,33	4,00	3,20	2,67	2,29	2,00	1,78	1,54	1,27	1,07	0,91	
			suction	6,91	5,18	4,14	3,02	2,22	1,70	1,34	1,09	0,90	0,75	0,64	
		SLS L/100	pressure	8,63	5,45	3,60	2,45	1,71	1,21	0,88	0,64	0,47	0,35	0,26	
			suction	8,94	5,72	3,83	2,65	1,88	1,36	1,00	0,75	0,57	0,44	0,34	
		SLS L/150	pressure	5,35	3,28	2,09	1,37	0,91	0,61	0,41	0,28	0,19	0,12	-	
			suction	5,66	3,54	2,32	1,57	1,08	0,76	0,54	0,39	0,28	0,21	0,15	
		SLS L/200	pressure	3,71	2,19	1,34	0,83	0,51	0,31	0,18	0,10	-	-	-	
			suction	4,02	2,46	1,57	1,03	0,68	0,46	0,31	0,21	0,14	-	-	
		II	ULS	pressure	5,33	4,00	3,20	2,67	2,29	2,00	1,78	1,54	1,27	1,07	0,91
				suction	6,91	5,18	4,14	3,02	2,22	1,70	1,34	1,09	0,90	0,75	0,64
			SLS L/100	pressure	8,63	5,45	3,60	2,45	1,71	1,21	0,88	0,64	0,47	0,35	0,26
				suction	8,63	5,45	3,60	2,45	1,71	1,21	0,88	0,64	0,47	0,35	0,26
	SLS L/150		pressure	5,35	3,28	2,09	1,37	0,91	0,61	0,41	0,28	0,19	0,12	-	
			suction	5,35	3,28	2,09	1,37	0,91	0,61	0,41	0,28	0,19	0,12	-	
	SLS L/200		pressure	3,71	2,19	1,34	0,83	0,51	0,31	0,18	0,10	-	-	-	
			suction	3,71	2,19	1,34	0,83	0,51	0,31	0,18	0,10	-	-	-	
	III		ULS	pressure	5,33	4,00	3,20	2,67	2,29	2,00	1,78	1,54	1,27	1,07	0,91
				suction	6,91	5,18	4,14	3,02	2,22	1,70	1,34	1,09	0,90	0,75	0,64
			SLS L/100	pressure	8,63	5,45	3,60	2,45	1,71	1,21	0,88	0,64	0,47	0,35	0,26
				suction	8,18	5,05	3,26	2,16	1,45	0,99	0,68	0,47	0,33	0,22	0,15
		SLS L/150	pressure	5,35	3,28	2,09	1,37	0,91	0,61	0,41	0,28	0,19	0,12	-	
			suction	4,90	2,88	1,75	1,07	0,65	0,39	0,22	0,11	-	-	-	
		SLS L/200	pressure	3,71	2,19	1,34	0,83	0,51	0,31	0,18	0,10	-	-	-	
			suction	3,26	1,79	0,99	0,53	0,26	-	-	-	-	-	-	

Multi-span system	I	ULS	pressure	3,68	2,67	2,09	1,71	1,42	1,04	0,80	0,63	0,51	0,42	0,35	
			suction	2,76	2,07	1,66	1,38	1,18	0,87	0,66	0,52	0,43	0,35	0,30	
		SLS L/100	pressure	9,39	6,45	4,71	3,51	2,66	2,06	1,62	1,28	1,03	0,83	0,67	
			suction	9,62	6,62	4,85	3,63	2,77	2,15	1,70	1,35	1,09	0,88	0,73	
		SLS L/150	pressure	5,96	4,05	2,95	2,17	1,64	1,25	0,96	0,75	0,60	0,47	0,38	
			suction	6,19	4,24	3,09	2,30	1,75	1,35	1,05	0,83	0,66	0,54	0,44	
		SLS L/200	pressure	4,25	2,86	2,07	1,51	1,12	0,85	0,65	0,49	0,38	0,30	0,24	
			suction	4,47	3,05	2,21	1,63	1,23	0,94	0,73	0,56	0,45	0,35	0,28	
		II	ULS	pressure	3,68	2,67	2,09	1,71	1,42	1,04	0,80	0,63	0,51	0,42	0,35
				suction	2,76	2,07	1,66	1,33	0,90	0,64	0,48	0,37	0,30	0,24	0,20
			SLS L/100	pressure	9,39	6,45	4,71	3,51	2,66	2,06	1,62	1,28	1,03	0,83	0,67
				suction	9,39	6,45	4,71	3,51	2,66	2,06	1,62	1,28	1,03	0,83	0,67
	SLS L/150		pressure	5,96	4,05	2,95	2,17	1,64	1,25	0,96	0,75	0,60	0,47	0,38	
			suction	5,96	4,05	2,95	2,17	1,64	1,25	0,96	0,75	0,60	0,47	0,38	
	SLS L/200		pressure	4,25	2,86	2,07	1,51	1,12	0,85	0,65	0,49	0,38	0,30	0,24	
			suction	4,25	2,86	2,07	1,51	1,12	0,85	0,65	0,49	0,38	0,30	0,24	
	III		ULS	pressure	3,68	2,67	2,09	1,71	1,42	1,04	0,80	0,63	0,51	0,42	0,35
				suction	2,76	2,07	1,66	1,46	0,80	0,48	0,30	0,20	0,14	0,10	-
			SLS L/100	pressure	9,39	6,45	4,71	3,51	2,66	2,06	1,62	1,28	1,03	0,83	0,67
				suction	9,05	6,17	4,49	3,33	2,51	1,92	1,49	1,17	0,93	0,74	0,60
		SLS L/150	pressure	5,96	4,05	2,95	2,17	1,64	1,25	0,96	0,75	0,60	0,47	0,38	
			suction	5,63	3,79	2,74	1,99	1,47	1,11	0,85	0,65	0,50	0,39	0,30	
		SLS L/200	pressure	4,25	2,86	2,07	1,51	1,12	0,85	0,65	0,49	0,38	0,30	0,24	
			suction	3,91	2,60	1,85	1,33	0,96	0,70	0,52	0,38	0,28	0,21	0,15	

I colour group:	very bright	RAL: 1015, 7035, 9002, 9010, 9016
II colour group:	bright	RAL: 5012, 9006, 6011
III colour group:	dark	RAL: 3000, 5010, 6029, 7016, 7024, 8017, 9007

In the case of dark colors, the total length of the board is limited. Details available from our sales representatives.

For other values of the internal temperature, thickness and material lining, etc., Please contact us to perform separate calculations.

Maximum allowable loads for a given span length:

GS insPIRe® U100

module: 1000 mm

External cladding thickness [mm]:	0,5		
Internal cladding thickness [mm]:	0,5		
Outdoor temperature (summer/winter) [°C]:	55	65	80
Indoor temperature (summer/winter) [°C]:	-20		
Minimum width of end support [mm]:	40		
Minimum width of the intermediate support [mm]:	60		

The minimum number of the screws on the end support :	2 + 1xPM-1
The minimum number of the screws on the intermediate support :	2 + 1xPM-1
Core material :	PIR
Cladding steel grade:	S220GD
Ultimate limit state (compare design loads)	ULS
Serviceability limit state (compare characteristic loads)	SLS

Static diagram	Colour group	Criterion	Maximum evenly distributed load [kN/m²]											
			Axial span of supports [m]											
			1,5	2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	6,5	
Single-span system	I	ULS	pressure	5,78	4,33	3,47	2,89	2,48	2,17	1,93	1,73	1,58	1,34	1,13
			suction	6,91	5,18	4,14	3,45	2,78	2,13	1,68	1,36	1,12	0,94	0,81
		SLS L/100	pressure	11,92	7,74	5,26	3,69	2,65	1,93	1,43	1,08	0,82	0,63	0,49
			suction	12,25	8,03	5,52	3,91	2,84	2,10	1,58	1,21	0,93	0,73	0,58
		SLS L/150	pressure	7,52	4,77	3,17	2,16	1,50	1,06	0,76	0,54	0,39	0,28	0,20
			suction	7,84	5,06	3,42	2,39	1,70	1,23	0,90	0,67	0,51	0,38	0,29
	SLS L/200	pressure	5,31	3,29	2,12	1,40	0,93	0,62	0,42	0,28	0,18	0,11	-	
		suction	5,64	3,58	2,37	1,62	1,13	0,79	0,57	0,41	0,29	0,21	0,15	
	II	ULS	pressure	5,78	4,33	3,47	2,89	2,48	2,17	1,93	1,73	1,58	1,34	1,13
			suction	6,91	5,18	4,14	3,45	2,78	2,13	1,68	1,36	1,12	0,94	0,81
		SLS L/100	pressure	11,92	7,74	5,26	3,69	2,65	1,93	1,43	1,08	0,82	0,63	0,49
			suction	11,92	7,74	5,26	3,69	2,65	1,93	1,43	1,08	0,82	0,63	0,49
		SLS L/150	pressure	7,52	4,77	3,17	2,16	1,50	1,06	0,76	0,54	0,39	0,28	0,20
			suction	7,52	4,77	3,17	2,16	1,50	1,06	0,76	0,54	0,39	0,28	0,20
	SLS L/200	pressure	5,31	3,29	2,12	1,40	0,93	0,62	0,42	0,28	0,18	0,11	-	
		suction	5,31	3,29	2,12	1,40	0,93	0,62	0,42	0,28	0,18	0,11	-	
	III	ULS	pressure	5,78	4,33	3,47	2,89	2,48	2,17	1,93	1,73	1,58	1,34	1,13
			suction	6,91	5,18	4,14	3,45	2,78	2,13	1,68	1,36	1,12	0,94	0,81
		SLS L/100	pressure	11,92	7,74	5,26	3,69	2,65	1,93	1,43	1,08	0,82	0,63	0,49
			suction	11,44	7,30	4,88	3,65	2,35	1,67	1,21	0,88	0,65	0,48	0,35
		SLS L/150	pressure	7,52	4,77	3,17	2,16	1,50	1,06	0,76	0,54	0,39	0,28	0,20
			suction	7,03	4,33	2,78	1,82	1,21	0,80	0,53	0,35	0,22	0,13	-
	SLS L/200	pressure	5,31	3,29	2,12	1,40	0,93	0,62	0,42	0,28	0,18	0,11	-	
		suction	4,83	2,85	1,73	1,06	0,64	0,37	0,19	-	-	-	-	

Multi-span system	I	ULS	pressure	4,08	2,97	2,32	1,90	1,60	1,34	1,02	0,80	0,65	0,53	0,45
			suction	2,76	2,07	1,66	1,38	1,18	1,04	0,85	0,67	0,54	0,45	0,38
		SLS L/100	pressure	12,69	8,79	6,49	4,94	3,82	2,99	2,38	1,91	1,55	1,27	1,05
			suction	12,94	8,99	6,65	5,07	3,94	3,10	2,47	2,00	1,63	1,34	1,11
		SLS L/150	pressure	8,13	5,59	4,11	3,11	2,38	1,85	1,46	1,16	0,94	0,75	0,62
			suction	8,37	5,79	4,27	3,25	2,50	1,96	1,55	1,25	1,01	0,83	0,68
	SLS L/200	pressure	5,85	3,99	2,92	2,19	1,66	1,28	1,00	0,79	0,63	0,50	0,40	
		suction	6,10	4,19	3,08	2,33	1,79	1,39	1,10	0,87	0,70	0,56	0,46	
	II	ULS	pressure	4,08	2,97	2,32	1,90	1,60	1,34	1,02	0,80	0,65	0,53	0,45
			suction	2,76	2,07	1,66	1,38	1,18	0,84	0,62	0,48	0,38	0,31	0,26
		SLS L/100	pressure	12,69	8,79	6,49	4,94	3,82	2,99	2,38	1,91	1,55	1,27	1,05
			suction	12,69	8,79	6,49	4,94	3,82	2,99	2,38	1,91	1,55	1,27	1,05
		SLS L/150	pressure	8,13	5,59	4,11	3,11	2,38	1,85	1,46	1,16	0,94	0,75	0,62
			suction	8,13	5,59	4,11	3,11	2,38	1,85	1,46	1,16	0,94	0,75	0,62
	SLS L/200	pressure	5,85	3,99	2,92	2,19	1,66	1,28	1,00	0,79	0,63	0,50	0,40	
		suction	5,85	3,99	2,92	2,19	1,66	1,28	1,00	0,79	0,63	0,50	0,40	
	III	ULS	pressure	4,08	2,97	2,32	1,90	1,60	1,34	1,02	0,80	0,65	0,53	0,45
			suction	2,76	2,07	1,66	1,13	0,68	0,43	0,29	0,20	0,14	0,11	-
		SLS L/100	pressure	12,69	8,79	6,49	4,94	3,82	2,99	2,38	1,91	1,55	1,27	1,05
			suction	12,32	8,49	6,25	4,74	3,64	2,84	2,24	1,78	1,44	1,17	0,95
		SLS L/150	pressure	8,13	5,59	4,11	3,11	2,38	1,85	1,46	1,16	0,94	0,75	0,62
			suction	7,75	5,29	3,86	2,90	2,20	1,69	1,32	1,04	0,82	0,65	0,53
	SLS L/200	pressure	5,85	3,99	2,92	2,19	1,66	1,28	1,00	0,79	0,63	0,50	0,40	
		suction	5,47	3,69	2,67	1,99	1,48	1,13	0,85	0,66	0,51	0,40	0,31	

I colour group:	very bright	RAL: 1015, 7035, 9002, 9010, 9016
II colour group:	bright	RAL: 5012, 9006, 6011
III colour group:	dark	RAL: 3000, 5010, 6029, 7016, 7024, 8017, 9007

In the case of dark colors, the total length of the board is limited. Details available from our sales representatives.

For other values of the internal temperature, thickness and material lining, etc., Please contact us to perform separate calculations.

Maximum allowable loads for a given span length:

GS insPIRe® U120

module: 1000 mm

External cladding thickness [mm]:	0,5		
Internal cladding thickness [mm]:	0,5		
Outdoor temperature (summer/winter) [°C]:	55	65	80
Indoor temperature (summer/winter) [°C]:	-20		
Minimum width of end support [mm]:	40		
Minimum width of the intermediate support [mm]:	60		

The minimum number of the screws on the end support :	2 + 1xPM-1
The minimum number of the screws on the intermediate support :	2 + 1xPM-1
Core material :	PIR
Cladding steel grade:	S220GD
Ultimate limit state (compare design loads)	ULS
Serviceability limit state (compare characteristic loads)	SLS

Static diagram	Colour group	Criterion	Maximum evenly distributed load [kN/m ²]											
			Axial span of supports [m]											
			1,5	2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	6,5	
Single-span system	I	ULS	pressure	6,22	4,67	3,73	3,11	2,67	2,33	2,07	1,87	1,70	1,56	1,36
			suction	6,91	5,18	4,14	3,45	2,96	2,55	2,02	1,63	1,34	1,14	0,97
		SLS L/100	pressure	14,85	9,85	6,86	4,93	3,61	2,70	2,04	1,56	1,21	0,95	0,75
			suction	15,18	10,16	7,13	5,17	3,83	2,88	2,21	1,71	1,34	1,07	0,85
		SLS L/150	pressure	9,46	6,17	4,22	2,96	2,13	1,55	1,14	0,85	0,64	0,48	0,36
			suction	9,79	6,47	4,49	3,20	2,34	1,73	1,31	0,99	0,77	0,60	0,47
	SLS L/200	pressure	6,77	4,33	2,89	1,98	1,38	0,97	0,69	0,49	0,35	0,24	0,17	
		suction	7,10	4,63	3,16	2,22	1,59	1,16	0,85	0,64	0,48	0,36	0,27	
	II	ULS	pressure	6,22	4,67	3,73	3,11	2,67	2,33	2,07	1,87	1,70	1,56	1,36
			suction	6,91	5,18	4,14	3,45	2,96	2,55	2,02	1,63	1,34	1,14	0,97
		SLS L/100	pressure	14,85	9,85	6,86	4,93	3,61	2,70	2,04	1,56	1,21	0,95	0,75
			suction	14,85	9,85	6,86	4,93	3,61	2,70	2,04	1,56	1,21	0,95	0,75
		SLS L/150	pressure	9,46	6,17	4,22	2,96	2,13	1,55	1,14	0,85	0,64	0,48	0,36
			suction	9,46	6,17	4,22	2,96	2,13	1,55	1,14	0,85	0,64	0,48	0,36
	SLS L/200	pressure	6,77	4,33	2,89	1,98	1,38	0,97	0,69	0,49	0,35	0,24	0,17	
		suction	6,77	4,33	2,89	1,98	1,38	0,97	0,69	0,49	0,35	0,24	0,17	
	III	ULS	pressure	6,22	4,67	3,73	3,11	2,67	2,33	2,07	1,87	1,70	1,56	1,36
			suction	6,91	5,18	4,14	3,45	2,96	2,55	2,02	1,63	1,34	1,14	0,97
		SLS L/100	pressure	14,85	9,85	6,86	4,93	3,61	2,70	2,04	1,56	1,21	0,95	0,75
			suction	14,36	9,40	6,46	4,57	3,29	2,41	1,79	1,35	1,02	0,78	0,60
		SLS L/150	pressure	9,46	6,17	4,22	2,96	2,13	1,55	1,14	0,85	0,64	0,48	0,36
			suction	8,97	5,72	3,81	2,60	1,81	1,27	0,89	0,63	0,44	0,31	0,21
	SLS L/200	pressure	6,77	4,33	2,89	1,98	1,38	0,97	0,69	0,49	0,35	0,24	0,17	
		suction	6,27	3,87	2,49	1,62	1,06	0,69	0,44	0,27	0,15	-	-	

Multi-span system	I	ULS	pressure	4,50	3,27	2,55	2,09	1,76	1,53	1,26	0,99	0,80	0,66	0,55
			suction	2,76	2,07	1,66	1,38	1,18	1,04	0,92	0,82	0,66	0,55	0,46
		SLS L/100	pressure	15,55	10,86	8,09	6,26	4,91	3,91	3,15	2,56	2,10	1,75	1,45
			suction	15,82	11,08	8,26	6,41	5,04	4,03	3,25	2,65	2,19	1,82	1,52
		SLS L/150	pressure	10,02	6,95	5,15	3,97	3,10	2,45	1,96	1,58	1,29	1,06	0,87
			suction	10,28	7,17	5,34	4,13	3,23	2,56	2,06	1,67	1,37	1,14	0,95
	SLS L/200	pressure	7,25	5,00	3,69	2,84	2,19	1,72	1,36	1,09	0,88	0,72	0,59	
		suction	7,52	5,22	3,86	2,98	2,33	1,84	1,47	1,19	0,96	0,79	0,65	
	II	ULS	pressure	4,50	3,27	2,55	2,09	1,76	1,53	1,26	0,99	0,80	0,66	0,55
			suction	2,76	2,07	1,66	1,38	1,18	1,04	0,79	0,60	0,48	0,39	0,32
		SLS L/100	pressure	15,55	10,86	8,09	6,26	4,91	3,91	3,15	2,56	2,10	1,75	1,45
			suction	15,55	10,86	8,09	6,26	4,91	3,91	3,15	2,56	2,10	1,75	1,45
		SLS L/150	pressure	10,02	6,95	5,15	3,97	3,10	2,45	1,96	1,58	1,29	1,06	0,87
			suction	10,02	6,95	5,15	3,97	3,10	2,45	1,96	1,58	1,29	1,06	0,87
	SLS L/200	pressure	7,25	5,00	3,69	2,84	2,19	1,72	1,36	1,09	0,88	0,72	0,59	
		suction	7,25	5,00	3,69	2,84	2,19	1,72	1,36	1,09	0,88	0,72	0,59	
	III	ULS	pressure	4,50	3,27	2,55	2,09	1,76	1,53	1,26	0,99	0,80	0,66	0,55
			suction	2,76	2,07	1,66	1,38	0,92	0,59	0,39	0,27	0,20	0,15	0,11
		SLS L/100	pressure	15,55	10,86	8,09	6,26	4,91	3,91	3,15	2,56	2,10	1,75	1,45
			suction	15,16	10,55	7,82	6,04	4,72	3,74	2,99	2,42	1,98	1,63	1,35
		SLS L/150	pressure	10,02	6,95	5,15	3,97	3,10	2,45	1,96	1,58	1,29	1,06	0,87
			suction	9,63	6,64	4,89	3,75	2,90	2,27	1,81	1,45	1,16	0,95	0,77
	SLS L/200	pressure	7,25	5,00	3,69	2,84	2,19	1,72	1,36	1,09	0,88	0,72	0,59	
		suction	6,86	4,68	3,42	2,61	2,00	1,55	1,21	0,95	0,75	0,61	0,48	

I colour group:	very bright	RAL: 1015, 7035, 9002, 9010, 9016
II colour group:	bright	RAL: 5012, 9006, 6011
III colour group:	dark	RAL: 3000, 5010, 6029, 7016, 7024, 8017, 9007

In the case of dark colors, the total length of the board is limited. Details available from our sales representatives.

For other values of the internal temperature, thickness and material lining, etc., Please contact us to perform separate calculations.

Maximum allowable loads for a given span length:

GS insPIRe® U140

module: 1000 mm

External cladding thickness [mm]:	0,5		
Internal cladding thickness [mm]:	0,5		
Outdoor temperature (summer/winter) [°C]:	55	65	80
Indoor temperature (summer/winter) [°C]:	-20		
Minimum width of end support [mm]:	40		
Minimum width of the intermediate support [mm]:	60		

The minimum number of the screws on the end support :	2 + 1xPM-1
The minimum number of the screws on the intermediate support :	2 + 1xPM-1
Core material :	PIR
Cladding steel grade:	S220GD
Ultimate limit state (compare design loads)	ULS
Serviceability limit state (compare characteristic loads)	SLS

Static diagram	Colour group	Criterion	Maximum evenly distributed load [kN/m ²]											
			Axial span of supports [m]											
			1,5	2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	6,5	
Single-span system	I	ULS	pressure	6,67	5,00	4,00	3,33	2,86	2,50	2,22	2,00	1,82	1,67	1,54
			suction	6,91	5,18	4,14	3,45	2,96	2,59	2,30	1,90	1,58	1,32	1,13
		SLS L/100	pressure	23,54	15,49	10,70	7,62	5,55	4,12	3,11	2,38	1,85	1,45	1,15
			suction	23,99	15,89	11,05	7,93	5,82	4,36	3,32	2,56	2,01	1,59	1,28
		SLS L/150	pressure	15,11	9,80	6,66	4,67	3,34	2,43	1,80	1,35	1,02	0,78	0,60
			suction	15,55	10,20	7,02	4,98	3,61	2,67	2,01	1,53	1,18	0,92	0,73
	SLS L/200	pressure	10,89	6,95	4,64	3,19	2,24	1,59	1,14	0,83	0,61	0,44	0,33	
		suction	11,33	7,35	5,00	3,50	2,51	1,83	1,35	1,01	0,76	0,58	0,45	
	II	ULS	pressure	6,67	5,00	4,00	3,33	2,86	2,50	2,22	2,00	1,82	1,67	1,54
			suction	6,91	5,18	4,14	3,45	2,96	2,59	2,30	1,90	1,58	1,32	1,13
		SLS L/100	pressure	23,54	15,49	10,70	7,62	5,55	4,12	3,11	2,38	1,85	1,45	1,15
			suction	23,54	15,49	10,70	7,62	5,55	4,12	3,11	2,38	1,85	1,45	1,15
		SLS L/150	pressure	15,11	9,80	6,66	4,67	3,34	2,43	1,80	1,35	1,02	0,78	0,60
			suction	15,11	9,80	6,66	4,67	3,34	2,43	1,80	1,35	1,02	0,78	0,60
	SLS L/200	pressure	10,89	6,95	4,64	3,19	2,24	1,59	1,14	0,83	0,61	0,44	0,33	
		suction	10,89	6,95	4,64	3,19	2,24	1,59	1,14	0,83	0,61	0,44	0,33	
	III	ULS	pressure	6,67	5,00	4,00	3,33	2,86	2,50	2,22	2,00	1,82	1,67	1,54
			suction	6,91	5,18	4,14	3,45	2,96	2,59	2,30	1,90	1,58	1,32	1,13
		SLS L/100	pressure	23,54	15,49	10,70	7,62	5,55	4,12	3,11	2,38	1,85	1,45	1,15
			suction	22,88	14,90	10,17	7,16	5,15	3,77	2,80	2,11	1,61	1,24	0,96
		SLS L/150	pressure	15,11	9,80	6,66	4,67	3,34	2,43	1,80	1,35	1,02	0,78	0,60
			suction	14,44	9,20	6,13	4,20	2,94	2,08	1,49	1,08	0,78	0,57	0,41
	SLS L/200	pressure	10,89	6,95	4,64	3,19	2,24	1,59	1,14	0,83	0,61	0,44	0,33	
		suction	10,22	6,35	4,12	2,73	1,83	1,24	0,83	0,56	0,37	0,23	0,14	

Multi-span system	I	ULS	pressure	5,01	3,66	2,86	2,34	1,97	1,70	1,49	1,28	1,02	0,84	0,69
			suction	2,76	2,07	1,66	1,38	1,18	1,04	0,92	0,83	0,75	0,63	0,53
		SLS L/100	pressure	24,80	17,25	12,79	9,79	7,61	6,01	4,81	3,89	3,17	2,62	2,17
			suction	25,15	17,54	13,02	9,98	7,77	6,15	4,94	4,01	3,28	2,71	2,25
		SLS L/150	pressure	16,08	11,14	8,23	6,27	4,85	3,81	3,03	2,44	1,97	1,62	1,34
			suction	16,42	11,41	8,45	6,46	5,02	3,95	3,16	2,55	2,08	1,71	1,42
	SLS L/200	pressure	11,72	8,07	5,95	4,52	3,47	2,71	2,15	1,71	1,38	1,12	0,92	
		suction	12,06	8,35	6,16	4,71	3,64	2,85	2,27	1,83	1,48	1,21	1,00	
	II	ULS	pressure	5,01	3,66	2,86	2,34	1,97	1,70	1,49	1,28	1,02	0,84	0,69
			suction	2,76	2,07	1,66	1,38	1,18	1,04	0,88	0,68	0,54	0,44	0,36
		SLS L/100	pressure	24,80	17,25	12,79	9,79	7,61	6,01	4,81	3,89	3,17	2,62	2,17
			suction	24,80	17,25	12,79	9,79	7,61	6,01	4,81	3,89	3,17	2,62	2,17
		SLS L/150	pressure	16,08	11,14	8,23	6,27	4,85	3,81	3,03	2,44	1,97	1,62	1,34
			suction	16,08	11,14	8,23	6,27	4,85	3,81	3,03	2,44	1,97	1,62	1,34
	SLS L/200	pressure	11,72	8,07	5,95	4,52	3,47	2,71	2,15	1,71	1,38	1,12	0,92	
		suction	11,72	8,07	5,95	4,52	3,47	2,71	2,15	1,71	1,38	1,12	0,92	
	III	ULS	pressure	5,01	3,66	2,86	2,34	1,97	1,70	1,49	1,28	1,02	0,84	0,69
			suction	2,26	1,72	1,40	1,19	0,97	0,62	0,41	0,29	0,21	0,15	0,12
		SLS L/100	pressure	24,80	17,25	12,79	9,79	7,61	6,01	4,81	3,89	3,17	2,62	2,17
			suction	24,29	16,85	12,45	9,51	7,36	5,79	4,61	3,71	3,02	2,47	2,05
		SLS L/150	pressure	16,08	11,14	8,23	6,27	4,85	3,81	3,03	2,44	1,97	1,62	1,34
			suction	15,56	10,72	7,88	5,99	4,60	3,59	2,84	2,26	1,82	1,47	1,21
	SLS L/200	pressure	11,72	8,07	5,95	4,52	3,47	2,71	2,15	1,71	1,38	1,12	0,92	
		suction	11,21	7,66	5,60	4,23	3,22	2,49	1,95	1,54	1,22	0,98	0,79	

I colour group:	very bright	RAL: 1015, 7035, 9002, 9010, 9016
II colour group:	bright	RAL: 5012, 9006, 6011
III colour group:	dark	RAL: 3000, 5010, 6029, 7016, 7024, 8017, 9007

In the case of dark colors, the total length of the board is limited. Details available from our sales representatives.

For other values of the internal temperature, thickness and material lining, etc., Please contact us to perform separate calculations.